# **SIEMENS**



# FDB181C Detector Base Product Manual

#### **Overview**

The FDB181C detector bases is a universal base. It's fixed on fire detection site and used for installations of FD181C series detectors:

- FDO181C smoke detector
- FDT181C heat detector

#### Characteristics

- Universal bases, applicable to both surface install and conceal install
- Large opening in the detector base for easy cable insertion
- Adopt environmental friendly material

#### Installation

The installation of a base should strictly follow the engineering design drawings. The bases should be evenly distributed.

#### Procedure of installation:


- 1. Insert the cables through the base and connect them to the terminals.
- 2. Fix the base to the ceiling with screws.

#### ■Note:


- The detector should be installed after the construction has been finished.
- In order to ensure the reliability of the connection between the base and the detector, please do not use U-type terminals.
- Twisted-pairs with the wiring requirement of 1.0~1.5mm² are recommended.

# **Building Technologies**

### **Dimensions**



## **Electric connection**



## **Technical data**

Connecting terminals	1.0 1.5 mm <sup>2</sup>	
Operating temperature		
Storage temperature	According to data of detectors	
Humidity		
Protection category EGB4208-93		
Color	White, RAL 9010	

# **Details for ordering**

Туре	Material No.	Part No.	Designation	Weight
FDB181C	S54320-F1-A1	100856213	Detector base	0.027 kg

Beijing Siemens Cerberus Electronics Limited No.1,Fengzhidonglu, Xibeiwang, HaiDian District, Beijing, 100094, China

Tel: +10 6476 8806 Fax: +10 6476 8899 © Data and design subject to change without notice.